



DUCTING AND COMPONENTS

To completion of the whole supply, Tama offers a wide range of galvanized steel sheet steel pipes and fittings of various sizes and thicknesses, available in the catalogue.



DUCTING AND COMPONENTS



STRAIGHT PIPES

Realized in galvanized steel sheet, with lengths from 1 m and 1.5 m. Sheet thicknesses from 6/10 to 10/10 with \varnothing 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



CIRCULAR BEND 30°, 45°, 60°, 90°

Realized in galvanized steel sheet, sheet thicknesses 8/10 with \varnothing from 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



BRANCHES 2 WAYS, 2 SYMMETRICAL WAYS AND 3 WAYS

Realized in galvanized steel sheet, with \varnothing from 80mm to 1000 mm. Available in smooth or flapped version.




SECTION CHANGES

Realized in galvanized steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth, flapped or flanged version.



CONE

Realized in galvanized steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth or flapped version.



MULTIPLE HEADS

Realized in galvanized steel sheet, sheet thicknesses from 8/ with \varnothing from 180mm to 400 mm. Available in smooth, flapped or flanged version.



OPEN TOP CAPS

Realized in galvanized steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 200mm to 1000 mm. Available in smooth or flapped version.



TERMINAL WITH PROTECTIVE GRILL

Realized in galvanized steel sheet, Sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth, flapped or flanged version.



CHINESE CHIMNEY CAPS

Realized in galvanized steel sheet, Sheet thicknesses from 8/10 to 15/10 with \varnothing from 120mm to 1000 mm. Available in smooth or flapped version.



SILENCERS

Realized in galvanized steel sheet, with lengths from 1 m and 1.5 m. sheet thicknesses from 8/10 to 10/10 with \varnothing 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



CIRCULAR COUPLINGS

Realized in galvanized steel sheet, sheet thicknesses from 8/10 to 10/10 with \varnothing from 80 mm to 1000 mm. Available in smooth or flapped version.




FLEXIBLE CONNECTOR WITH PVC CANVAS

Realized in galvanized steel sheet, sheet thicknesses from 6/10 with \varnothing from 100 mm to 1000 mm. Available in smooth, flanged or flapped version.




CLOSING CAP

Realized in galvanized steel sheet, with \varnothing from 80mm to 1000 mm.



CLAMPS - WALL SUPPORTS

Clamp for tubing, widths from 300 mm to 1400 mm. Painted clamp for chimney, \varnothing from 300 mm to 1000 mm.



BRACKET COLLARS

PAINTED COLLARS

Realized in painted steel sheet, \varnothing from 300 mm to 1000 mm.

COLLAR

Collar realized in zinc-coated steel sheet, \varnothing from 80 mm to 400 mm.

MONOCOLLAR

Realized in galvanized steel sheet, \varnothing from 180 mm to 1000 mm.



FLANGES

CIRCULAR PRESSED FLANGES

Realized in galvanized steel sheet, \varnothing from 80 mm to 600 mm.

ANGULAR PROFILE FLANGES

Realized in galvanized steel sheet, \varnothing from 80 mm to 600 mm.



GUILLOTINE DAMPER

MANUAL

Light range: \varnothing from 80 mm to 600 mm.
Heavy-duty range: \varnothing from 350 mm to 800 mm.

PNEUMATIC

Light range: \varnothing from 80 mm to 300 mm.
Heavy-duty range: \varnothing from 350 mm to 800 mm.

ELECTRO-PNEUMATIC

Light range: \varnothing from 80 mm to 300 mm. Heavy-duty range: \varnothing from 350 mm to 800 mm.
Realized in galvanized steel sheet, available in smooth, flapped or flanged version.



MANUAL, PNEUMATIC AND ELECTRO-PNEUMATIC BUTTERFLY DAMPER

Realized in galvanized steel sheet, \varnothing from 80 mm to 600 mm. Available in smooth, flapped or flanged version.



NON-RETURN VALVE

Realized in galvanized steel sheet, \varnothing from 200 mm to 600 mm. Available in smooth, flapped or flanged version.



FLOOR-SWEPS

Realized in galvanized steel sheet, \varnothing from 120 mm to 150 mm. Available in smooth, flapped or flanged version.



FLEXIBLE HOSE

Realized in strengthened and transparent polyurethane with steel spiral.



HOSE CLAMPS

Realized in galvanized steel sheet, \varnothing from 60 mm to 400 mm.